

**STREET STANDARDS
COLLECTOR STREETS**

| ITEM | LOW VOLUME | HIGH VOLUME | INDUSTRIAL | COMMERCIAL |
|--|-------------|--------------|------------|------------|
| Traffic (Vehicles/Day) | 1500 - 5000 | 5000 - 15000 | > 5000 | > 5000 |
| Number of Traffic Lanes | 2 | 4 | 3 | 3 |
| Taffic Lane Width (Feet) | 11 | 11 | 11 | 11 |
| Parking Lane Width (Feet) | 9 | 10 | 10 | 10 |
| Pavement Width [Back to Back of Curb (Feet)] | 36 | 47 | 36 - 45 | 36 - 45 |
| Median Width (Feet) | N/A | N/A | N/A | N/A |
| Border Area Width (Feet) | 12 | 12.5 | 12.5 min. | 12.5 min. |
| Right-of-Way Width (Feet) | 60 | 70 | 70 - 90 | 70 - 90 |
| Sidewalks (Feet) | 4 | 4 | 5 | 5 |
| Desirable Street Spacing (Miles) | 1/4 mile | 1/4 mile | 1/4 mile | 1/4 mile |
| Minimum Intersection Spacing | 200 feet | 660 feet | 660 feet | 660 feet |

NOTE:

On-street parking is assumed in all cases except wher off-street parking is demonstrated as adequate.

STREET STANDARDS